

# E75 Gearmeerde thermokoppel verlengkabel -30°C tot 85°C

## Specificaties

<b>Isolatiemateriaal</b>	Draadisolatie, hoge kwaliteit geëxtrudeerd PVC
<b>Elektrische scherm</b>	Twee lagen van aluminium mylar tape met aarde draad
<b>Binnenmantel</b>	PVC
<b>Armering</b>	Verzinkt staaldraad gevlecht (SWB) 0.3mm
<b>Buitenmantel</b>	Hoge kwaliteit geëxtrudeerd PVC
<b>Vorm</b>	Rond
<b>Vochtbestendigheid</b>	Goed
<b>Vlambestendigheid</b>	Goed
<b>Mechanische sterkte</b>	Uitstekend
<b>Temperatuurgrenzen</b>	-30/+85°C

## Geleiders

<b>Geleider uitvoering</b>	A) Massief of B) Litze
<b>Aderdikte</b>	Massief 1.3 mm Litze 1.5 mm <sup>2</sup> (48x0.2 mm)

## Kalibratie

<b>Thermokoppel type</b>	K, T, J, E, U, L, N, B, R of S
<b>Nauwkeurigheid</b>	Voldoet aan IEC 584 en ANSI MC 96.1

## Kleurcode

Volgens thermokoppel kalibratie

## Afmetingen

Outside diameter	9.8	11	mm
Weight	140	150	kg/km



### International Thermocouple Colour Codes

Thermocouple Extension Type	ANSI	BS	DIN	NFC	JIS	IEC
<b>JX + Iron - Constantan</b>						
<b>KX + Chromel - Alumel</b>						
<b>TX + Copper - Constantan</b>						
<b>EX + Chromel - Constantan</b>						
<b>NX + Nicrosil - Nisil</b>						
<b>SX + Copper - Alloy 11</b>						
<b>BX + Copper-S - Copper-E</b>						

Weteringweg 10, 2641 KM Pijnacker, The Netherlands  
Phone: +31 15 362 12 00, E-mail: mail@thermo.nl  
www.thermo-electra.com

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

