

TE1210 Mini thermokoppel contrastekker

Toepassing	
Connector	Thermokoppel en Pt100 circuits
Ontwerp	Geschikt voor kleine draden en minimale aderisolatie
Materialen	Glas gevuld thermoplastische lichaam met originele thermokoppel materiaal contacten
Temperatuurbereik	
Temperatuurgrens	Maximaal 200°C
Constructie	
Body	Glasgevuld thermoplastisch materiaal
Ontwerp	Robuust op lichaam ontwerp
Gegoten isolatieschotten	Voorkomen kortsluiting
Draad afmeting	
Accepteert draden	Vanaf 0,002 mm tot 0,6 mm
Kabelmantel diameter	Maximaal 4,5 mm.
Accessoires	
Optionele accessoires	Zie aparte datasheet
Kleurcode	



Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

** For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors*

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1210