

# TE1210C Mini jack keramisch tot 650°C



## Toepassing

Connector	Thermokoppel en Pt100 circuits
Ontwerp	Geschikt voor kleine draden en minimale aderisolatie
Materialen	Stekker keramiek en de pinnen thermokoppelmateriaal

## Temperatuurbereik

Temperatuurgrens	Maximum 650Å°C.
------------------	-----------------

## Constructie

Body	High purity alumina body material
Ontwerp	Robuust ontwerp
Gegoten isolatieschotten	Voorkomen kortsluiting

## Draad afmeting

Accepteert draden	Vanaf 0002 mm. tot 0,6 mm
Kabelmantel diameter	Maximaal 4,5 mm.

## Accessoires

Optionele accessoires	Zie aparte datasheet
-----------------------	----------------------

## Kleurcode

Beschikbare kleuren	Alleen wit thermokoppelkalibratie door gekleurde stip
---------------------	---

Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

\* For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1210C