

TE1034 Paneelinbouw chassisdeel, 3 polig Thermokoppel of Pt100

Toepassing

Contra connector panel	Thermokoppel en Pt100 circuits
Third connection	Thermokoppel met aarde of 3-draads Pt100
Contacten	Veerbelaste thermokoppel of Cu contacten
Materialen	Glas gevuld thermoplastisch lichaam met Cu, of origineel thermokoppel contacten contacten


Temperatuurbereik

Temperatuurgrens	Maximaal 200 °C
Body	Glasgevuld thermoplastisch materiaal
Gegoten isolatieschotten	Voorkomen kortsluiting

Draad afmeting

Accepteert draden	Van 0,2 mm. tot 2,0 mm.
--------------------------	-------------------------

Kleurcode




Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

* For Pt. 6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.



H9-2Rev.0 7/07