

TE1044 Thermokoppel chassisdeel, rond

Toepassing

Contra connector panel	Thermokoppel en Pt100 circuits
Contacten	Veerbelaste thermokoppel contacten
Materialen	Glas gevuld thermoplastische lichaam met originele thermokoppel inhoudelijke contacten

Temperatuurbereik

Temperatuurgrens	Maximaal 200 °C
-------------------------	-----------------

Constructie

Body	Glasgevuld thermoplastisch materiaal
Ontwerp	Roestvrijstalen beugel met 2 schroeven
Gegoten isolatieschotten	Voorkomen kortsluiting

Draad afmeting

Accepteert draden	Van 0,2 mm. tot 2,0 mm.
--------------------------	-------------------------

Kleurcode

Kleur van de body	IEC of ANSI kleur
--------------------------	-------------------



Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

* For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1044