

TE1260D Mini dubbele thermokoppel stekker



Toepassing

Connector	Voor het aansluiten van 2 thermokoppels op 1 stekker
Ontwerp	Geschikt voor kleine draden en minimale aderisolatie
Materialen	Glasgevuld kunststof body met origineel thermokoppel materiaal pinnen

Temperatuurbereik

Temperatuurgrens	Maximaal 200°C
------------------	----------------

Constructie

Body	Glasgevuld thermoplastisch materiaal
Ontwerp	Robuust ontwerp
Gegoten isolatieschotten	Voorkomen kortsluiting

Draad afmeting

Accepteert draden	Vanaf 0.002mm tot 0.6mm
Kabel diameter	Maximaal 4.5mm

Accessoires

Optionele accessoires	Zie aparte datasheet
-----------------------	----------------------

Kleurcode

Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

** For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors*

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1260D